


Nota Note	Posi-tion	Gewijzigd van Modified from	Datum Date	Ingev./Goedg. Intr./Appd.																																																																																																																																																									
01		Sheet 2 modified	88-03-15																																																																																																																																																										
<table border="0" style="width:100%"> <tr> <td></td> <td>GA</td> <td>GA</td> <td>GA</td> <td>GA</td> </tr> <tr> <td></td> <td>11</td> <td>15</td> <td>18</td> <td>22</td> </tr> <tr> <td></td> <td>125</td> <td>125</td> <td>125</td> <td>125</td> </tr> </table> <p>Reference conditions -----</p> <table border="0" style="width:100%"> <tr> <td>1.Absolute inlet pressure.....</td> <td>bar</td> <td>1</td> <td>1</td> <td>1</td> <td>1</td> </tr> <tr> <td>2.Relative air humidity.....</td> <td>%</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>3.Air inlet temperature.....</td> <td>C</td> <td>20</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>4.Normal effective working pressure.....</td> <td>bar</td> <td>8.5</td> <td>8.5</td> <td>8.5</td> <td>8.5</td> </tr> </table> <p>The inlet conditions are specified at the air inlet grating outside the canopy.</p> <p>Limitations 1) -----</p> <table border="0" style="width:100%"> <tr> <td>1.Maximum effective working pressure.....</td> <td>bar</td> <td>8.8</td> <td>8.8</td> <td>8.8</td> <td>8.8</td> </tr> <tr> <td>2.Minimum effective working pressure.....</td> <td>bar</td> <td>4</td> <td>4</td> <td>4</td> <td>4</td> </tr> <tr> <td>3.Maximum allowable inlet temperature.....</td> <td>C</td> <td>40</td> <td>40</td> <td>40</td> <td>40</td> </tr> </table> <p>Performance data 1) -----</p> <table border="0" style="width:100%"> <tr> <td>1.Motor shaft speed.....</td> <td>r/min</td> <td>1765</td> <td>1765</td> <td>1765</td> <td>1765</td> </tr> <tr> <td>2.Free air delivery at reference conditions 2)</td> <td>L/s</td> <td>25.5</td> <td>36.0</td> <td>44.5</td> <td>50.4</td> </tr> <tr> <td>Free air delivery at effective working pressures stated 2).....</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>8.8 bar</td> <td>L/s</td> <td>25.2</td> <td>35.7</td> <td>44.2</td> <td>50.1</td> </tr> <tr> <td>8.0 bar</td> <td>L/s</td> <td>26.0</td> <td>36.5</td> <td>45.0</td> <td>51.0</td> </tr> <tr> <td>6.0 bar</td> <td>L/s</td> <td>27.8</td> <td>38.4</td> <td>47.0</td> <td>52.9</td> </tr> <tr> <td>4.0 bar</td> <td>L/s</td> <td>29.6</td> <td>40.4</td> <td>49.0</td> <td>54.9</td> </tr> <tr> <td>3.Shaft input at reference conditions.....</td> <td>kW</td> <td>12.7</td> <td>16.9</td> <td>20.6</td> <td>23.3</td> </tr> <tr> <td>Shaft input at effective working pressures stated.....</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>8.8 bar</td> <td>kW</td> <td>12.9</td> <td>17.2</td> <td>21.1</td> <td>23.8</td> </tr> <tr> <td>8.0 bar</td> <td>kW</td> <td>12.4</td> <td>16.4</td> <td>20.0</td> <td>22.6</td> </tr> <tr> <td>6.0 bar</td> <td>kW</td> <td>10.8</td> <td>14.2</td> <td>17.2</td> <td>19.3</td> </tr> <tr> <td>4.0 bar</td> <td>kW</td> <td>9.1</td> <td>12.0</td> <td>14.5</td> <td>16.1</td> </tr> <tr> <td>4.Power consumption at no load</td> <td>kW</td> <td>3.1</td> <td>4.2</td> <td>5.2</td> <td>6.0</td> </tr> <tr> <td>5.Specific energy requirement at ref. cond.</td> <td>J/L</td> <td>498</td> <td>469</td> <td>463</td> <td>462</td> </tr> <tr> <td>Specific energy requirement at effective working</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>						GA	GA	GA	GA		11	15	18	22		125	125	125	125	1.Absolute inlet pressure.....	bar	1	1	1	1	2.Relative air humidity.....	%	0	0	0	0	3.Air inlet temperature.....	C	20	20	20	20	4.Normal effective working pressure.....	bar	8.5	8.5	8.5	8.5	1.Maximum effective working pressure.....	bar	8.8	8.8	8.8	8.8	2.Minimum effective working pressure.....	bar	4	4	4	4	3.Maximum allowable inlet temperature.....	C	40	40	40	40	1.Motor shaft speed.....	r/min	1765	1765	1765	1765	2.Free air delivery at reference conditions 2)	L/s	25.5	36.0	44.5	50.4	Free air delivery at effective working pressures stated 2).....						8.8 bar	L/s	25.2	35.7	44.2	50.1	8.0 bar	L/s	26.0	36.5	45.0	51.0	6.0 bar	L/s	27.8	38.4	47.0	52.9	4.0 bar	L/s	29.6	40.4	49.0	54.9	3.Shaft input at reference conditions.....	kW	12.7	16.9	20.6	23.3	Shaft input at effective working pressures stated.....						8.8 bar	kW	12.9	17.2	21.1	23.8	8.0 bar	kW	12.4	16.4	20.0	22.6	6.0 bar	kW	10.8	14.2	17.2	19.3	4.0 bar	kW	9.1	12.0	14.5	16.1	4.Power consumption at no load	kW	3.1	4.2	5.2	6.0	5.Specific energy requirement at ref. cond.	J/L	498	469	463	462	Specific energy requirement at effective working					
	GA	GA	GA	GA																																																																																																																																																									
	11	15	18	22																																																																																																																																																									
	125	125	125	125																																																																																																																																																									
1.Absolute inlet pressure.....	bar	1	1	1	1																																																																																																																																																								
2.Relative air humidity.....	%	0	0	0	0																																																																																																																																																								
3.Air inlet temperature.....	C	20	20	20	20																																																																																																																																																								
4.Normal effective working pressure.....	bar	8.5	8.5	8.5	8.5																																																																																																																																																								
1.Maximum effective working pressure.....	bar	8.8	8.8	8.8	8.8																																																																																																																																																								
2.Minimum effective working pressure.....	bar	4	4	4	4																																																																																																																																																								
3.Maximum allowable inlet temperature.....	C	40	40	40	40																																																																																																																																																								
1.Motor shaft speed.....	r/min	1765	1765	1765	1765																																																																																																																																																								
2.Free air delivery at reference conditions 2)	L/s	25.5	36.0	44.5	50.4																																																																																																																																																								
Free air delivery at effective working pressures stated 2).....																																																																																																																																																													
8.8 bar	L/s	25.2	35.7	44.2	50.1																																																																																																																																																								
8.0 bar	L/s	26.0	36.5	45.0	51.0																																																																																																																																																								
6.0 bar	L/s	27.8	38.4	47.0	52.9																																																																																																																																																								
4.0 bar	L/s	29.6	40.4	49.0	54.9																																																																																																																																																								
3.Shaft input at reference conditions.....	kW	12.7	16.9	20.6	23.3																																																																																																																																																								
Shaft input at effective working pressures stated.....																																																																																																																																																													
8.8 bar	kW	12.9	17.2	21.1	23.8																																																																																																																																																								
8.0 bar	kW	12.4	16.4	20.0	22.6																																																																																																																																																								
6.0 bar	kW	10.8	14.2	17.2	19.3																																																																																																																																																								
4.0 bar	kW	9.1	12.0	14.5	16.1																																																																																																																																																								
4.Power consumption at no load	kW	3.1	4.2	5.2	6.0																																																																																																																																																								
5.Specific energy requirement at ref. cond.	J/L	498	469	463	462																																																																																																																																																								
Specific energy requirement at effective working																																																																																																																																																													
Benaming Name		AML DATA	06115	Geheim.klasse Secrecy Class																																																																																																																																																									
Materiaal Material		GA11,-15,-18,-22 Pack Arr. 2 - 60 Hz		1102 K/ 3																																																																																																																																																									
Behandeling Treatment		PRELIMINARY		CAD																																																																																																																																																									
	Schaal Scale	Familie Family	0083 1010 00	A4																																																																																																																																																									
	Getekend Drawn by	URBDEG	Ruw nr. Blank nr.																																																																																																																																																										
Overgemaakt/Transferred from	Std gez./chd.	Ruw gew. Blank wt.	Kg	Afg gew. Fini wt.																																																																																																																																																									
		Identificatie/Designation		Blad/Sheet 01 (03)																																																																																																																																																									
		Desig. no. / Proj. no.		Datum/Date																																																																																																																																																									
		APPROVED		88-01-12																																																																																																																																																									
		9820 0976 03																																																																																																																																																											

Dit document is onze eigendom en zal niet zonder toestemming worden gewijzigd, kopiëerd, gereproduceerd of verspreid. Het is de eigendom van de fabrikant en de afzender aanvaardt de aansprakelijkheid voor schade van welke aard ook voortvloeiende uit het gebruik van dit document. This document is our property and shall not be altered, copied, used for manufacturing or communicated to any other person or company.



Eigenaar Drawing owner
AIR

MEDUSA - 9820 0976 03, p.01, ed.01 - Valid : (unknown)

Nota Note	Posi-tion	Gewijzigd van Modified from	Datum Date	Ingev./Goedg. Intr./Appd.
01		72,72,73,74 were 69,72,74,75 Canopy dimensions was overall dimensions	88-03-15	000

pressures stated.....	8.8 bar	J/L	512	482	477	475
	8.0 bar	J/L	477	449	444	443
	6.0 bar	J/L	388	370	366	365
	4.0 bar	J/L	307	297	296	293
6.Compressed air temperature at outlet valve	C		32	34	34	35
7.Typical oil content of compressed air....	mg/m3		5	5	5	5
8.Sound pressure level, measured according to CAGI PNEUROF test code with a tolerance of +3 dBA under free field conditions at 1 m distance.....	dB(A)		72	72	73	74

Design data

Compressor

1.Number of compression stages.....	-	1	1	1	1
2.Male rotor speed.....	r/min	1378	1811	2171	2415

Unit

1.Oil capacity.....	l	10	10	10	10
2.Dimensions of air inlet gratings (2 off):					
-Height.....	mm	330	330	330	330
-Width.....	mm	318	318	318	318
3.Dimensions of cooling air outlet grating:					
-Height.....	mm	660	660	660	660
-Width.....	mm	318	318	318	318
4.Cooling air flow referred to air inlet grating.....	m3/s	0.39	0.51	0.67	0.76
5.Allowable pressure drop in cooling air ducts.....	Pa	30	30	30	30
6.Dimension of compressed air outlet valve (threaded).....	G	1	1	1 1/4	1 1/4
7.Inner diameter of condensate drain pipe..	mm	12	12	12	12
8.Maximum diameter of mains cable.....	mm	46	46	46	46
9.Canopy dimensions:					
-Length.....	mm	1118	1118	1118	1118

Dit document is onze eigendom en zal niet zonder toestemming worden gewijzigd, gereproduceerd, gekopieerd, verspreid of anderszins openbaar gemaakt. Het is de verantwoordelijkheid van de gebruiker om de afbeeldingen te kopiëren en te verspreiden. Dit document is our property and shall not be altered, copied, reproduced, disseminated or otherwise made public without our permission. It is the user's responsibility to copy and disseminate the drawings.

Benaming Name		AML DATA		06115		Geheim.klasse Secrecy Class			
Materiaal Material		GA11,-15,-18,-22 Pack Arr. 2 - 60 Hz		1102 K/ 3		CAD			
Behandeling Treatment		PRELIMINARY		A4		Vergelijk Compare		Eigenaar Drawing owner	
		Schaal Scale		Familie Family		0083 1010 00		URBDEG	
Overgenomen/Transferred from		Getekend Drawn by		Ruw gew. Blank wt.		Kg		Afg gew. Fini wt.	
		Std gez./chd.		Kg		Kg		Identificatie/Designation	
		Des. gez. by		Kg		Kg		Blad/Sheet 02 (03)	
		88-01-12		88-01-12		88-01-12		9820 0976 03	
		APPROVED							

