




“Big Red”
T-520M

**Taylor Industrial Truck
Standard Specifications**

Rated Capacity 52,000-lbs. (**23,587 kg**)

48-in. (**1,219 mm**) Load Center

170-in. (**4,318 mm**) Wheelbase





“Big Red” T-520M

GENERAL	1	Manufacturer	Manufacturer's Name	TAYLOR	
	2	Model	Manufacturer's Designation	T-520M	
				English	Metric
	3	Capacity	Rated Capacity lb (kg)	52,000	23,587
	4	Load Center	Distance in (mm)	48	1,219
	5	Power Type	Gas, LPG, Or Diesel	Diesel	
	6	Tire Type	Cushion, Pneumatic Front / Rear	Pneumatic / Pneumatic	
DIMENSIONS	7	Wheels	Number (X = Driven) Front / Rear	4X / 2	
	8	Upright Lift	Standard Lift (Top Of Fork) in (mm)	137	3,480
	9	Forks	Thickness in (mm)	5	127
	9A		Width in (mm)	10	254
	9B		Length in (mm)	96	2,438
	10	Tilt Angle	Standard Upright - Forward / Backward deg.°	15 / 10	
	11	Overall Dimensions	Length To Face Of Forks in (mm)	249.25	6,331
	12		Width (Standard Tires) in (mm)	120	3,048
	13		Height, Standard Upright Lowered in (mm)	155	3,937
	14		Height, Standard Upright Extended in (mm)	221	5,613
	15		Height To Top Of Counterweight in (mm)	72	1,829
	16		Height To Top Of A-Frame in (mm)	129	3,277
	17	Turning Radius	Minimum Outside in (mm)	235	5,969
	17A		Minimum Inside in (mm)	26	660
	18	Load Distance	Center of Wheel To Face Of Forks in (mm)	42.25	1,073
	19	Aisle Width	(Add Load Length For 90° Stacking) in (mm)	277.25	7,042
PERFORMANCE	20	Stability	Comply With ANSI?	Yes	
	21	Speeds	Travel Speed - Maximum Forward mph (km/h)	15.7	25.3
	22		Lift Speed - No Load fpm (m/s)	56	0.28
	22A		Lift Speed - With Load fpm (m/s)	49	0.25
	23		Lowering Speed - No Load / With Load fpm (m/s)	60	.3
	24	Drawbar Pull	Powershift (Maximum At Stall) lb (kN)	35,300	157
	25	Gradeability	Powershift (Maximum At Stall) No Load %	30.2	
WEIGHT	25A		Powershift (Maximum At Stall) With Load %	28.4	
	26	Ttl. Apprx. Wt.	Standard Truck lb (kg)	73,800	33,476
	27	Axle Loading	Static With Rated Load - Front lb (kg)	113,965	51,695
	27A		Static With Rated Load - Rear lb (kg)	11,835	5,368
	27B		Static With No Load - Front lb (kg)	34,350	15,581
	27C		Static With No Load - Rear lb (kg)	39,350	17,849
WHEELS / TIRES	28	Tires	Number - Front / Rear	4 / 2	
	29		Size - Front	14.00 x 25 - 20 PR	
	30		Size - Rear	14.00 x 25 - 20 PR	
	31	Wheelbase	Distance in (mm)	170	4,318
	32	Tread	Center Of Outside (Dual) Tires - Front in (mm)	86	2,184
	32A		Center Of Tires - Rear in (mm)	91	2,311
	33	Ground Clearance	No Load At Lowest Point in (mm)	12	305
	34		No Load At Center Of Wheelbase in (mm)	18	457
	35	Brakes	Service / Parking - Method Of Control	Foot / Hand	
	36		Service / Parking - Method Of Operation	Air / Spring	
POWER UNIT / XMSN	37	Battery	Volts / Ampere Hours (2 Batteries) V/Ah	12 / 2300	
	38	Internal Combustion Engine	Make / Model	Cummins QS8.3-C230	
	39		Output - Intermittent Per SAE Standards hp (kW)	230	172
	40		Governed Speed - With Load rpm	2200	
	41		Cycle / Number Of Cylinders / Displacement cu in (L)	4 / 6 / 506	4 / 6 / 8.3
	42	Clutch	Type	Declutch	
	43	Gear Change	Type	Hand	
	44	Transmission	Number Of Speeds - Forward / Reverse	3 / 3	
	45		Type	Powershift	
	46	Relief Press.	For Attachments psi (bar)	1500	103
	47		Width Across Counterweight in (mm)	108	2,743
	48		Standard Fork Spread in (mm)	100	2,540
	49		Ground To Top Of Carriage in (mm)	79	2,007
	50		Load Moment in-lbs (m-kg)	4,693,000	54,070

† NOTE: Performance specifications are for trucks equipped as described on the back page of this specification sheet. Performance specifications are affected by the condition of the vehicle, its components, and the nature and condition of the operating area. If these specifications are critical, the proposed application should be discussed with your Taylor sales representative.

“Big Red” T-520M

Mast Dimensions (inches / millimeters)						
2-Stage ULTRA-VU Telescopic Mast	Optional Lift Height (8)		OAHL (13)		OAHR (14)	
	English	Metric	English	Metric	English	Metric
	137	3,480	155	3,937	221	5,613
	161	4,089	167	4,242	245	6,223
	185	4,699	179	4,547	269	6,833
	221	5,613	197	5,004	305	7,747



"Big Red" T-520M

Engine

Cummins QSC8.3-C230, 6-cylinder electronic turbocharged, charge air after cooled (air to air) diesel engine has 506 cu-in. (8.3 L) displacement, 4.49-in. (114 mm) bore x 5.31-in. (135 mm) stroke. Rated power 230-hp (172 kW) at 2200 rpm (all engine ratings are based on SAE standard ambient conditions). Maximum power of 250-hp (186 kW) at 2000 rpm. Peak torque is 800 ft-lbs. (1,085 N-m) at 1500 rpm. Emission certification: US EPA Tier III, Carb Tier III, EU Stage III.

Standard features are electronic diagnostic, maintenance monitor, fuel/water separator, engine/transmission protection system, fuel economy and reduced emissions.

Fuel tank capacity is 60 gallons (227 L).

Air Cleaner

The dry air cleaner has a safety element and restriction indicator.

Cooling System

Coolant recovery cooling system has an extra large down flow radiator for maximum efficiency. The wide fin spacing reduces dirt build-up and provides optimum engine cooling.

Electrical, Instrumentation, and Accessories

The one-piece instrument panel flips down for easy servicing and is pre-wired to accommodate heavy-duty accessories. All wiring is color coded.

The unit has a 12-volt electrical system. Standard equipment includes a key-type anti-restart ignition system, 2 heavy-duty batteries, 100-amp alternator, mechanical pressure gauges, electrical temperature gauges, reset circuit breakers, lighted instruments, horn, work lights (two front, and two rear), key-switch actuated amber strobe light, reverse-actuated warning alarm and tilt steering.

Gauges include fuel level, ammeter, hourmeter, air pressure, engine oil pressure, engine coolant temperature, transmission oil pressure, and transmission oil temperature. Lights included are seat belt light, low air light, parking brake light, and step lights.

Transmission

The three-speed, fully reversing, modulated, powershift transmission has declutch and electric shift control. Brakes behind declutch. The filler pipe dipstick and large, heavy-duty, oil filter are easily accessible. Separate air-to-oil cooler. The integrally built torque converter has constant mesh gear sets actuated by hydraulic clutch packs. An automatic powershift control is standard.

Drive Axle

The heavy-duty planetary type drive axle housing is welded to the frame.

Steer Axle

The single hydraulic cylinder design steer axle, with heavy-duty links from the cylinder ram directly to tapered roller bearing mounted spindles, has tapered wheel and kingpin bearings. All joints are sealed, can be lubricated, and never need adjusting.

Brake System

The force cooled, wet disc, air/hydraulic actuated, service brakes are mounted on the drive axle. The transmission is equipped with a spring-applied drum brake for parking.

Chassis

The all welded frame has an integral, sloped, counterweight and tubular A-frame. A spring-assisted hood and hinged doors provide easy access to service points.

The canopy is integral with the operator station base. The center mount operator station is standard and can be optionally located offset to the left side of the vehicle. The tinted, unbreakable, Lexan top with steel crossbars provides maximum visibility and protection. The suspension seat with an operator seat belt is adjustable.

Hydraulic System

The large capacity hydraulic tank has a spin-on tank breather, suction strainers, return line filters, and replaceable elements in the tank. The hydraulic system utilizes transmission-driven gear type pumps. The tank refill capacity is 72 gallons (273 L). The tilt lock valve prevents mast drift and reduces torsional stress. Dual lift cylinders have chrome-plated rods and self-adjusting packing. Control levers are conveniently located. Valves are controlled with hydraulic remotes.

Mast, Carriage, and Rollers

The 11-ft. (3.4 m) ULTRA-VU telescopic, nested-channel mast, with two nested, hidden multiple-leaf lift chains, is constructed of high-strength steel for minimum weight. The two lifting eyes and bolt-on caps permit safe, easy removal of the mast.

The "C" type carriage has a high strength-to-weight ratio. The forks are pin-mounted and fully adjustable from 100-in. (2,540 mm) outside to 2-in. (51 mm) inside the center brace.

Main rollers and chain rollers have shielded, tapered, roller bearings. The carriage side wear pads are adjustable to compensate for wear. All rollers can be lubricated.

Forks

The forks are hammer forged from heat treated alloy steel. Standard size:

5-in. x 10-in. x 96-in. (127 mm x 254 mm x 2438 mm).

This vehicle is certified to meet the applicable design and performance criteria required for Powered Industrial Trucks in OSHA Safety and Health Standards, Title 29 CFR, Part 1910.178, and the applicable design and performance requirements in ANSI B56.1 that were in effect at the time of manufacture. These standards also apply to the user and should be adhered to while operating this vehicle.

All specifications are subject to change without notice. Some operating data may be affected by the condition of the operating area. If these specifications are critical, contact the factory.