

COUPLING, ***, 1-5/16 IN X 3/8 IN, TAP PARTIAL
COUPLING, ***, 7/8 IN BORE, COMPLETE, 3/16 IN KEYWAY LP-347-AV-BM, 200 SERIES
COUPLING, ***, CARBON STEEL 4C 5-S NSA
COUPLING, PIPE, 4 IN, CAST IRON
COUPLING, PIPE, 8 IN, CAST IRON
COUPLING, SHAFT, ***, 1.375 IN X 1.250 IN BORE W/ 5/16 IN X 5/32 IN KEYWAY, W/ 1/4 IN X 1/8 IN KEYWAY
COUPLING, SHAFT, ***, CARBON STEEL, CW ROTATION, F/ GAS FAN TURNING GEAR
COUPLING, SHAFT, ***, ROUGH BORE, CONSISTS OF (2) HUBS & (1) CENTER
COUPLING, SHAFT, ***, SS, CUSTOM BORE, DISC PACK SERIES 63
COUPLING, SHAFT, FLEXIBLE TAPERED GRID, 2-1/8 IN BORE, 6.42 IN OD, 5.12 IN LG, STEEL, VERTICAL SPLIT, 1/2 IN SQ KEYWAY, STEELFLEX
COUPLING, SHAFT, FLEXIBLE TAPERED GRID, 3.436 IN X 2.623 IN BORE, 9.88 IN OD, 9.69 IN LG, STEEL, HORIZONTAL SPLIT, STEELFLEX W/ 7/8 IN X 15/32 IN KEYWAY, W/ 5/8 IN X 11/32 IN KEYWAY
COUPLING, SHAFT, GEAR AUX OIL PUMP MOTOR DRIVEN
COUPLING, SHAFT, GRID TYPE, 1-1/2 IN X 1-5/8 IN BORE, 5-13/16 IN OD, 5-1/8 IN LG, STEEL, 1060T10, COMPLETE ASSY, W/ 3/8 IN KEYWAY
COUPLING, SHAFT, GRID TYPE, 7/16 IN BORE, 4-5/32 IN OD, 3-7/8 IN LG, STEEL, 1030T10 SIZE, COMPLETE ASSY, STEELFLEX MIN BORE, CONSISTING OF (2) 1030TXRSB HUBS & (1) 1030T10 COVER & GRID
COUPLING, SHAFT, HALF, ***, ELASTOMERIC TYPE R
COUPLING, SHAFT, HALF, ***, ELASTOMERIC, HUB TYPE C
COUPLING, SHAFT, HALF, ***, ELASTOMERIC, HUB TYPE E
COUPLING, SHAFT, HALF, GEAR, FLEX, ROUGH STOCK BORE, 7 IN OD, 4-1/4 IN LG, STEEL, DOUBLE ENGAGEMENT, LIFELIGN, HUB
COUPLING, SHAFT, HALF, JAW, 1-1/4 IN BORE, 4.50 IN OD, CAST IRON
COUPLING, SHAFT, HALF, JAW, 1-7/8 IN BORE, 4.50 IN OD, CAST IRON, 1/2X1/4 IN KW
COUPLING, SHAFT, JAW, 5/8 IN X 5/8 IN BORE, 1.75 IN OD, 2.13 IN LG, SINTERED IRON, BUNA-N INSERT LOV - 00111705
COUPLING, TUBE, 1 IN TO 1-1/8 IN